


LUXURY VINYL TILE

CREATION 30 CLIC New: Available in January 2019

▶ CREATION 30 CLIC



PUR+ MATT



Easy maintenance

4D DESIGN

STRUCTURED EMOSS & BEVEL



Ultra realistic surface

MATT SURFACE



Natural look

CRISTAL WEAR LAYER



High definition design & color

DESIGNS

Wide variety of planks or tiles

DUO CORE TECHNOLOGY

1 RESILIENT COMFORT CORE



Noise absorption



Soft underfoot

2 RIGID CORE



The best stability
Fiber glass inside



No adhesive




Renovation ceramic
4 mm joint

CLIC REVOLUTION 100% VERTICAL



30% Faster



Heavy load resistance



Waterproof joints


Please refer to Gerflor's installation guidelines



Underlay Gerflor Acoustic
More details on gerflor.com

Romus Tools
Anti-bounce mallet - Fitter Knife - LVT Roller

CREATION 30 CLIC New: Available in January 2019



214x1239 mm | 242x1461 mm | 391x729 mm | PUR+ Matt | 100% recyclable

CREATION 30 CLIC are synthetic, decorative, flexible, antistatic, abrasion group T floorcoverings available in tiles and planks, with bevelled edges. They consist in a 0.4 mm thick transparent wear layer, a design film of 2 m width to have more variety in the design and a Duo Core Technology, made with a rigid core back layer reinforced with a fiber veil, combined with a flexible core top layer to provide softness and comfort surface. The overall thickness is 4.5 mm.

They benefit from a cross-linked polyurethane surface treatment (**PUR+ MATT**), making maintenance easier and eliminating the need for initial polishes.

CREATION 30 CLIC is an interlocking floorcovering assembled with a vertical system on the long and short side for a quick and solid installation. The resistance to use (commercial / industrial use) of 23/32 according to EN-ISO 10874 and has B_{fl-s}1 class for smoke emission according to EN 13501-1.

CREATION 30 CLIC is made with phthalate free plasticizers, except recycled content. It is 100% recyclable and made with 55% of recycled content. It is 100% compliant with REACH. The product emission rate of organic compounds is < 10µg/m³ (TVOC <28 days - ISO 16000-6).

			CREATION 30 CLIC
DESCRIPTION			
Total thickness	EN ISO 24346 (EN 428)	mm	4.50
Thickness of wearlayer	EN ISO 24340 (EN 429)	mm	0.40
Weight	EN ISO 23997 (EN 430)	g/sq.m	7385
Plank size	EN ISO 24342 (EN 427)	mm	214x1239 / 242x1461
Tile size	EN ISO 24342 (EN 427)	mm	391x729
CLASSIFICATION			
Norm / Product specification	-	-	EN ISO 10582 (EN 649)
European classification	EN ISO 10874 (EN 685)	class	32 - 41
Fire rating	EN 13501-1	class	B _{fl-s} 1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear group	NF 189	group	T
Type Binder content	ISO 10582	type	I
Room impact	NF S 31074	dB	78
Impact sound insulation	EN ISO 717-2	dB	4
Dimensional stability	EN ISO 23999 (EN 434)	%	≤ 0.15
Residual indentation	EN ISO 24343-1 (EN 433)	mm	≤ 0.10
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.k)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	PUR+ Matt
Chemical products resistance	EN ISO 26987 (EN 423)	-	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg / m ³	<10
CE MARKING			
CE	EN 14041		